product details

# DST TWIST 5W/825 E14

| | |
|---|---|
| Product description: | DST TWIST 5W/825 E14 |
| Product code: | 4008321939661 |
| Quantity: | Blister (BLI) contains 1 Piece (PCE) |

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321939661

| Applications | |
|---|---|
| Dimmable | No |

| Certificates & Standards | |
|---|---|
| EEI - Energy Label | A |

| General Description | |
|---|---|
| Mercury-free | No |
| Lamp mercury content | 2.0 mg |
| Base (standard designation) | E14 |
| Recycling | Yes |
| Cleaning instruction in case of breakage | What to do if a lamp containing mercury breaks |

| Technical - Electrical Data | |
|---|---|
| Rated lamp efficacy (HF data) | Under clarification by authority and standardization body |
| Rated power factor λ | 0.60 |
| Construction wattage | 5 |
| Rated number of switching cycles | 5000 |
| Claimed equivalent incand. lamp power | 27 W |
| Nominal wattage | 5 W |
| Nominal voltage (product) | 230 V |
| Operating frequency | 50...60 Hz |
| Nominal current (product) | 35 mA |
| Construction current | 35 mA |

| Technical - Geometries | |
|---|---|
| Length | 94.00 mm |
| Overall length | 94.00 mm |
| Diameter | 7.60 mm |
| Tube diameter | T2 |
| Construction length | 94.00 mm |

| Technical - Lifespan | |
|---|---|
| Rated lamp life time | 8000 h |
| Nominal lamp life time | 8000 h |

| Technical - Light Technical Data | |
|---|---|
| Lumen main.fact.at end of nom.life time | 0.65 |
| Rated warm-up time (60 %) | 40 s |
| Nominal luminous flux | 250 lm |
| Rated color rendering index (Ra) | >=80 |
| Rated starting time | 2.0 s |
| Rated luminous flux | 275 lm |


Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH

product details

# DST TWIST 5W/825 E14

| Technical - Light Technical Data | |
|---|---|
| Luminous flux | 270 lm |
| Light color | 825 |
| Rated color temperature | 2500 K |
| Color rendering index Ra | 80...89 |
| Light color as per EN 12464-1 | Warm Comfort Light |
| Color rendering group | 1B |
| Color temperature | 2500 K |

**Packaging units**

| Product code | Packaging type and content | Dimensions in h x w x l | Gross weight | Volume |
|---|---|---|---|---|
| 4008321939661 | Blister contains 1 Piece | 75,000 mm x 38,000 mm x 170,000 mm | 40,400 g (0,000 g) | 0,599 Cubic dec. |
| 4008321939678 | Shipping carton box contains 10 Piece | 134,000 mm x 191,000 mm x 196,000 mm | 558,000 g (0,000 g) | 4,718 Cubic dec. |

**Modern energy-saving lamp in a compact half-spiral form**

The compact OSRAM DULUXSTAR MINI TWIST energy-saving lamps have impressively high luminous efficacy and a fascinating appearance. They have an average life of up to 8,000 hours.

- NEW: Warm Comfort Light - warm energy-saving light similar to that of an incandescent lamp
- Average life is up to 8,000 hours (switching cycle: 165 min on, 15 min off) for OSRAM DULUXSTAR MINI TWIST, that corresponds to as much as 8 years at approx. 2.7 hours per day
- Up to 80 % less energy consumption compared with ordinary light bulbs
- Attractive and compact design, therefore ideal for use in open luminaires

OSRAM DULUXSTAR MINI TWIST lamps are not suitable for use with external dimmers or electronic switches.

Use outdoors only in enclosed and ventilated luminaires.

Not available in all countries.


Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH